

IPILITE[®] coresshield

Increase your productivity with
Perlite Molded Insulation



Superior Thermal Performance,
Eco-Friendly, and Corrosion Resistant



WHAT IS PERLITE?

Perlite is a naturally occurring volcanic mineral that expands when heated, creating a lightweight, porous material ideal for insulation.



WHY CHOOSE PERLITE PIPE INSULATION?

- 1. Superior Thermal Performance**
Reduces heat loss and improves energy efficiency.
- 2. Corrosion Resistance**
Hydrophobic properties prevent moisture accumulation.
- 3. Fire Safety**
Non-combustible and withstands high temperatures.
- 4. Eco-Friendly**
Sustainable and recyclable material.
- 5. Lightweight and Easy to Install**
Simplifies handling and reduces structural load.



CORESHIELD TECHNICAL DETAIL

Service Temperature	(Min-Max, °C)	-20 ~ 650
Density	(Max, kg/m ³)	220 ~ 250
Thermal Conductivity (ASTM C177-19)	(Max, W/mK)	0.0673

BASIC CHEMICAL COMPOSITION

SiO ₂	70 - 74%
Al ₂ O ₃	11 - 14%
Na ₂ O ₃	2 - 3.5%
K ₂ O	3 - 5.3%
CaO	0.1 - 1.1%



PRODUCT REVIEW

IPILITE CORESHIELD is a molded insulation that has the water resistant properties that helps protect pipe and equipment from corrosion under insulation. It has the ability to withstand high temperatures, up to 650°C as per ASTM C610.



1. Hydrophobic Nature

Perlite is hydrophobic, meaning it repels water. This property helps in preventing moisture from entering the insulation, which is crucial in preventing CUI. When water is retained in the insulation, it can lead to corrosion of the underlying metal substrate.

2. Corrosion Inhibitors

IPILITE CORESHIELD, contain built-in corrosion inhibitors. These inhibitors help in preventing corrosion by creating a protective layer on the metal surface, especially in high-temperature applications where stress corrosion cracking is a concern.

3. Water Absorption Resistance

Perlite has low water absorption properties, which means it does not absorb significant amounts of moisture even when exposed to high temperatures. This reduces the risk of water-induced corrosion under the insulation.

CORESHIELD SIZE , THICKNESS & SEGMENT

*Standard product length : 600mm

SIZE BOARD		THICKNESS (mm)						
No	Width	30	40	50	65	75	90	100
1	150 mm	●	●	●	●	●	●	●
2	300 mm	●	●	●	●	●	●	●

CORESHIELD SIZE , THICKNESS & SEGMENT

*Standard product length : 600mm

SIZE PIPE		THICKNESS (mm)						
No	Inch	30	40	50	65	75	90	100
1	1/2	● (2)	● (2)	● (2)				
2	3/4	● (2)	● (2)	● (2)	● (2)	● (2)	● (2)	● (2)
3	1	● (2)	● (2)	● (2)	● (2)		● (2)	● (2)
4	1 1/4	● (2)	● (2)	● (2)		● (2)		
5	1 1/2	● (2)	● (2)	● (2)			● (2)	● (2)
6	2	● (2)	● (2)	● (2)			● (2)	● (2)
7	2 1/2	● (2)	● (2)	● (2)				
8	3		● (2)	● (2)				
9	3 1/2	● (2)	● (2)	● (2)			● (2)	● (2)
10	4	● (2)	● (2)	● (2)		● (2)	● (2)	● (2)
11	4 1/2	● (2)						
12	5	● (2)	● (2)	● (2)		● (2)	● (2)	● (2)
13	6	● (2)	● (2)	● (2)	● (2)	● (2)	● (2)	● (3)
14	7	● (3)	● (3)	● (3)	● (3)	● (3)		
15	8	● (3)		● (3)	● (3)	● (3)	● (4)	● (4)
16	9	● (3)	● (3)	● (3)	● (3)	● (3)	● (4)	● (4)
17	10	● (3)	● (3)	● (3)	● (3)			● (4)
18	11	● (4)	● (4)	● (4)			● (5)	● (5)
19	12	● (4)	● (4)	● (4)	● (4)	● (4)	● (5)	● (5)



+62 818 1888 8422



www.ipijaya.com



info@ipijaya.com